

QCRV2.E103997 - OUTLET BUSHINGS AND FITTINGS - COMPONENT

Outlet Bushings and Fittings - Component

See General Information for Outlet Bushings and Fittings - Component

HUMMEL AG

E103997

LISE-MEITNER-STRASSE 2
79211 DENZLINGEN, GERMANY

Cord connectors Model(s) LC M 20 G UR, LCM 12 B UR, LCM 12 G UR, LCM 16 B E UR, LCM 16 B UR, LCM 16 G E UR, LCM 16 G UR, LCM 20 B UR, LCM 20 G E UR, LCM 25 B UR, LCM 25 G UR, LCM 32 B UR, LCM 32 G UR, LCM 40 B UR, LCM 40 G UR, LCM 50 B UR, LCM 50 G UR, LCM 63 B UR, LCM 63 G UR, LCM12B, LCM12G, LCM16B, LCM16G, LCM20B, LCM20G, LCMM 20 B E UR, LCN 1/0 B UR, LCN 1/0 G UR, LCN 10 B UR, LCN 10 G UR, LCN 12 B E UR, LCN 12 B UR, LCN 12 G E UR, LCN 12 G UR, LCN 34 B UR, LCN 34 G UR, LCN 38, LCN 5/4 B UR, LCN 5/4 G UR, LCN 54 B UR, LCN 54 G UR, LCN 6/4 B UR, LCN 6/4 G UR, LCN 64 B UR, LCN 64 G UR, LCN 1/2 BE UR B UR, LCN 1/2 BE UR G UR, LCN 1/2 GE UR B UR, LCN 1/2 GE UR G UR, LCN 3/4 B UR, LCN 3/4 G UR, LCN1/2B, LCN1/2G, LCN3/8B, LCN3/8G, LCP 07 B UR, LCP 07 G UR, LCP 09 B UR, LCP 09 G UR, LCP 11 B UR, LCP 11 G UR, LCP 13 B UR, LCP 13 G UR, LCP 16 B UR, LCP 16 G UR, LCP 21 B UR, LCP 21 G UR, LCP 29 B UR, LCP 29 G UR, LCP 36 B UR, LCP 36 G UR, LCP 42 B UR, LCP 42 G UR, LCP 48 B UR, LCP 48 G UR, LCP07B, LCP07G, LCP09B, LCP09G, LCP11B, LCP11G, LCP13B, LCP13G, LCP16B, LCP16G

Liquid tight fittings for cords Model(s) MLCM12, MLCM16, MLCM20

Liquid tight fittings for cords (sizes M12x1.5, M16x1.5) Model(s) HSK-K/Metrica-P

Liquid tight fittings for cords (sizes PG-7, PG-9, PG-11, 3/8 in NPT, M12x1.5 M16x1.5) Model(s) HSK-EH, HSK-Elbow, HSK-Flex, HSK-Flex-Elbow, HSK-K, HSK-K-Ex, HSK-K-PVDF, HSK-KE, HSK-KE-Flex, HSK-KR, HSK-KR-Flex

Liquid-tight flexible cord connectors Model(s) 1.607.1200.50, 1.607.1600.50, 1.607.2000.50, 1.607.2013.50, 1.607.2500.50, 1.607.3200.50, 1.618.1200.30, 1.618.1200.31, 1.618.1200.50, 1.618.1200.51, 1.618.1600.30, 1.618.1600.31, 1.618.1600.50, 1.618.1600.51, 1.618.2000.30, 1.618.2000.31, 1.618.2500.30, 1.618.2500.31, 1.618.3200.30, 1.618.3200.31, 1.683.1200.30, 1.683.1200.31, 1.683.1200.50, 1.683.1200.51, 1.683.1600.30, 1.683.1600.31, 1.683.1600.50, 1.683.1600.51, 1.683.2000.30, 1.683.2000.31, 1.683.2500.30, 1.683.2500.31, 1.683.3200.30, 1.683.3200.31

Liquid-tight flexible cord connectors (sizes PG7, PG7 Flex, PG9, PG9 Flex, PG11, PG11 Flex, 3/4 in NPT, 3/8 in NPT, 3/8 in NPT Flex, M12x 1.5, M16 x 1.5) Model(s) HSK-E-FLEX, HSK-INOX-PG, HSK-M-FLEX-EMV

Multiliquid-tight flexible cord connectors Model(s) HSK-ELBOW MULTI, HSK-EX MULTI, HSK-FLEX MULTI, HSK-FLEX-ELBOW MULTI, HSK-K MULTI, HSK-KE MULTI, HSK-KE-EX MULTI, HSK-KE-FLEX MULTI, HSK-KR MULTI, HSK-KR-FLEX MULTI, HSK-M MULTI, HSK-M-EMV MULTI, HSK-M-EMV-EX MULTI, HSK-M-EX MULTI, HSK-ME MULTI, HSK-ME-EX MULTI, HSK-MZ MULTI, HSK-W MULTI, M12X1.5, M16X1.5, M20X1.5, M25X1.5, M32X1.5, M40X1.5, M50X1.5, M63X1.5, NPT 1, NPT 1-1/2, NPT 1-1/4, NPT 1/2, NPT 3/4, NPT 3/8, PG11, PG13, PG13.5, PG16, PG21, PG29, PG36, PG42, PG48, PG7, PG9

Outlet Bushings and Fittings Model(s) 1.740.1203.50, 1.740.1603.50, 1.740.1603.51, 1.740.2003.50, 1.740.2003.51, 1.740.2003.54

Investigated to ANSI/UL 514B 6th ed.(last revised 2014-06-04)

Liquid-tight flexible cord connectors (sizes PG7, PG9, PG11, 3/4 in NPT, 3/8 in NPT, M12x 1.5, M16 x 1.5) Model(s) HSK-INOX, HSK-INOX-EMV-Ex, HSK-INOX-EX, HSK-INOX-PVDF, HSK-INOX/-PVDF-Ex, HSK-M, HSK-M-EMV, HSK-M-EMV-D, HSK-M-EMV-Ex, HSK-M-EX, HSK-M-FLEX, HSK-M-FLEX-EMV, HSK-M-PVDF, HSK-M-PVDF-EMV, HSK-M-PVDF-EMV-Ex, HSK-M/-PVDF-Ex, HSK-MZ, HSK-MZ-EMV, HSK-MZ-EMV-Ex, HSK-MZ-EX, HSK-MZ/-PVDF-Ex

Liquid-tight flexible cord connectors (sizes PG7, PG9, PG11, 3/4 in NPT, 3/8 in NPT, M12x 1.5, M16 x 1.5) Model(s) HSK-E-FLEX, HSK-INOX-EMV

Outlet Bushings and Fittings Model(s) HSK-INOX-PVDF-EMV

Marking: Company name or trademark  ,  , EcoTec and model designation.

Last Updated on 2017-05-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"